





MODELS		DIMENSIONS					HEATING TECHNOLOGY					FLUE CONNECTION	
	Page	Weight (lbs)	External dimensions width/ depth/ height (")	Dimensions of the fireplace firebox width/ depth (")	Dimensions of the bakeoven firebox width/ depth (")	Stone type	Maximum amount of wood/ heating (lbs)	Stored energy (Btu)	Maximum heating Sq. Feet	Electrical elements / Firebox technology of the fireplace			Recommended flue (")
													
FIREPLACES		TULIKIVI-WHIRLBOX											
KIPITTI/C	15	2640	35 ³ / ₈ / 19 ⁵ / ₈ / 60 ¹ / ₄	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	29	174012	750	○	-	●	6" or 7"
KIPITTI/C2 L	15	3146	52 / 19 ⁵ / ₈ / 60 ¹ / ₄	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	29	174012	750	○	-	●	6" or 7"
KIRAKKA	13	2585	35 ³ / ₈ / 19 ⁵ / ₈ / 60 ¹ / ₄	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	29	174012	750	○	-	●	6" or 7"
KOUTA/C	25	3179	43 ¹ / ₈ / 31 ⁵ / ₈ / 69 ⁵ / ₈	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	33	201308	860	○	-	●	6" or 7"
KOUTA/R	25	3234	43 ¹ / ₈ / 31 ⁵ / ₈ / 69 ⁵ / ₈	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	33	201308	860	○	-	●	6" or 7"
KOUTA/M	25	3421	47 ¹ / ₈ / 32 ¹ / ₄ / 69 ⁵ / ₈	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	39	232016	860	○	-	●	6" or 7"
LAINIO/C	15	3773	39 / 22 ¹ / ₂ / 60 ¹ / ₄	14 ¹ / ₈ / 10 ⁵ / ₈	-	TB	39	232016	860	○	-	●	6" or 7"
LOUHI	13	2827	35 ³ / ₈ / 18 ¹ / ₈ / 60 ¹ / ₄	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	29	174012	750	○	-	●	6" or 7"
OLOS/C	15	3960	39 / 22 ¹ / ₂ / 62	14 ¹ / ₈ / 10 ⁵ / ₈	-	TS	39	232016	970	○	-	●	6" or 7"
PAHTA/C	17	3465	39 / 20 ⁵ / ₈ / 69 ⁵ / ₈	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	39	232016	860	○	-	●	6" or 7"
PAHTA/F	17	3784	39 / 22 ¹ / ₂ / 69 ⁵ / ₈	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	39	232016	860	○	-	●	6" or 7"
PAHTA/M L	17	3630	39 / 22 ¹ / ₂ / 69 ⁵ / ₈	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	39	232016	860	○	-	●	6" or 7"
PAHTA/R	17	3542	39 / 20 ⁵ / ₈ / 69 ⁵ / ₈	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	39	232016	860	○	-	●	6" or 7"
SARMI/C	19	4059	42 ¹ / ₂ / 21 ¹ / ₂ / 69 ⁵ / ₈	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	44	266136	970	○	-	●	6" or 7"
SARMI/R	19	4070	42 ¹ / ₂ / 21 ¹ / ₂ / 69 ⁵ / ₈	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	44	266136	970	○	-	●	6" or 7"
SARMI/R + HM001	19	5390	68 ¹ / ₈ / 21 ¹ / ₂ / 69 ⁵ / ₈	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	44	266136	970	○	-	●	6" or 7"
SARMI/R + KM001	19	4587	68 ¹ / ₈ / 21 ¹ / ₂ / 69 ⁵ / ₈	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	44	266136	970	○	-	●	6" or 7"
SILO/C	14	2635	35 ³ / ₈ / 19 ¹ / ₄ / 60 ¹ / ₄	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	29	174012	750	○	-	●	6" or 7"
SILO/C + TM001	15	3949	50 ³ / ₄ / 19 ¹ / ₄ / 71 ¹ / ₂	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	39	232016	750	○	-	●	6" or 7"
SILO/R	15	2640	35 ³ / ₈ / 19 ¹ / ₄ / 60 ¹ / ₄	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	29	174012	750	○	-	●	6" or 7"
SONKA/C	11	4785	54 ³ / ₈ / 23 ⁵ / ₈ / 60 ¹ / ₄	14 ¹ / ₈ , 20 ¹ / ₂ / 10 ⁵ / ₈	-	TK	44	266136	1080	○	-	●	6" or 7"
VALKIA	11	3080	42 ¹ / ₂ / 19 ⁵ / ₈ / 60 ¹ / ₄	14 ¹ / ₈ , 20 ¹ / ₂ / 10 ⁵ / ₈	-	TK	33	201308	860	○	-	●	6" or 7"
VALKIA + KM002	11	3960	66 ¹ / ₈ / 19 ⁵ / ₈ / 60 ¹ / ₄	14 ¹ / ₈ , 20 ¹ / ₂ / 10 ⁵ / ₈	-	TK	33	201308	860	○	-	●	6" or 7"
VALKIA + PM001	11	3527	76 ³ / ₈ / 19 ⁵ / ₈ / 60 ¹ / ₄	14 ¹ / ₈ , 20 ¹ / ₂ / 10 ⁵ / ₈	-	TK	33	201308	860	○	-	●	6" or 7"
VASA	13	2618	35 ³ / ₈ / 19 ⁵ / ₈ / 60 ¹ / ₄	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	29	174012	750	○	-	●	6" or 7"
VASA + KM002	13	3498	59 / 19 ⁵ / ₈ / 60 ¹ / ₄	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	29	174012	750	○	-	●	6" or 7"
VASA + PM001	13	3058	69 ¹ / ₄ / 19 ⁵ / ₈ / 60 ¹ / ₄	14 ¹ / ₈ / 10 ⁵ / ₈	-	TK	29	174012	750	○	-	●	6" or 7"
VASKI	11	3080	42 ¹ / ₂ / 19 ⁵ / ₈ / 60 ¹ / ₄	14 ¹ / ₈ , 20 ¹ / ₈ / 10 ⁵ / ₈	-	TK	33	201308	860	○	-	●	6" or 7"
FIREPLACES		TULIKIVI-FLAT GRATE											
FIORINA	21	4994	30 ³ / ₈ / 59 ⁵ / ₈ / 69 ⁵ / ₈	15 / 15	-	TK	51	259312	970	○	●	-	7" or 8"
GEMINI	21	4664	37 ³ / ₄ / 53 ³ / ₄ / 74 ³ / ₈	15 / 15	-	TK	46	242252	970	○	●	-	7" or 8"
KTU 1137/3D	25	2486	37 ¹ / ₈ / 30 ⁷ / ₈ / 50 ³ / ₄	11 ³ / ₄ / 11 ³ / ₄	-	TK	29	150128	750	○	●	-	6" to 8"
KTU 1330/50	25	3542	38 ³ / ₈ / 31 ³ / ₄ / 65	8 ¹ / ₄ , 20 ¹ / ₈ / 13 ⁵ / ₈	-	TK	35	184248	860	○	●	-	7" or 8"
KTU 1410/1	25	3300	40 ³ / ₄ / 29 ¹ / ₈ / 65	14 ¹ / ₈ / 11 ¹ / ₄	-	TK	33	170600	860	○	●	-	6" to 8"
KTU 2253	21	4950	56 ⁷ / ₈ / 43 ⁵ / ₈ / 67 ³ / ₈	20 ³ / ₈ / 18 ¹ / ₈	-	TK	48	259312	970	○	●	-	7" or 8"
KURU R	21	4026	51 ³ / ₈ / 22 ¹ / ₂ / 67 ⁷ / ₈	15 ¹ / ₈ / 11 ³ / ₄	-	TS	33	174012	860	○	●	-	6" to 8"
T750/C	23	1980	24 ³ / ₄ / 17 ³ / ₄ / 56 ³ / ₄	14 ¹ / ₈ / 9 ¹ / ₄	-	TK	20	102360	650	-	●	-	6"
T750/M	23	1980	24 ³ / ₄ / 17 ³ / ₄ / 56 ³ / ₄	14 ¹ / ₈ / 9 ¹ / ₄	-	TK	20	102360	650	-	●	-	6"
TTU 2700/2	21	9702	61 ³ / ₈ ¹⁾ / 50 ³ / ₄ ¹⁾ / 86 ¹ / ₄	16 ¹ / ₂ / 24 ³ / ₄	-	TK	81	419676	1400	○	●	-	8"
TU 900	23	2244	30 ³ / ₄ / 18 ⁷ / ₈ / 48 ³ / ₈	12 ⁵ / ₈ / 9 ¹ / ₄	-	TK	22	116008	750	○	●	-	6" to 8"
TU 930	23	2112	26 / 21 ¹ / ₄ / 54 ¹ / ₈	12 ³ / ₈ / 11 ³ / ₄	-	TK	22	109184	750	○	●	-	6" to 8"
TU 1000/7	23	3806	48 ³ / ₈ / 18 ⁷ / ₈ / 62 ⁵ / ₈	15 ³ / ₈ / 10	-	TK	37	197896	860	○	●	-	6" to 8"
TU 1030/5D	19	2222	28 ³ / ₈ / 21 ⁷ / ₈ / 50 ³ / ₄	11 ³ / ₄ / 11 ³ / ₄	-	TK	26	139892	750	○	●	-	6" to 8"
TU 1237/51	19	3344	35 ³ / ₈ / 23 / 65	8 ¹ / ₄ , 20 ¹ / ₈ / 13 ⁵ / ₈	-	TK	33	174012	860	○	●	-	7" or 8"

MODELS		DIMENSIONS					HEATING TECHNOLOGY					FLUE CONNECTION	
	Page	Weight (lbs)	External dimensions width/ depth/ height (")	Dimensions of the fireplace firebox width/ depth (")	Dimensions of the bakeoven firebox width/ depth (")	Stone type	Maximum amount of wood/ heating (lbs)	Stored energy (Btu)	Maximum heating Sq. Feet	Electrical elements / Firebox technology of the fireplace			Recommended flue (")
FIREPLACE/BAKEOVENS													
KTLU 2037/53	29	5324	46 ⁵ / ₈ / 37 ¹ / ₂ / 68 ¹ / ₂	16 ¹ / ₂ / 15 ³ / ₈	16 ¹ / ₂ / 17 ¹ / ₂	TK	53	276372	970	○	●	-	8"
KTLU 2050/1	29	4114	45 ³ / ₄ / 31 ⁵ / ₈ / 65	16 ¹ / ₂ / 12 ³ / ₈	16 ¹ / ₂ / 13 ⁵ / ₈	TK	42	214956	860	○	●	-	7" or 8"
SALVIA DELI	29	4004	45 ¹ / ₄ / 32 ¹ / ₂ / 67 ³ / ₄	15 ³ / ₈ / 13 ¹ / ₈	16 ¹ / ₂ / 11 ³ / ₈	TK	40	208132	860	○	●	-	7" or 8"
TLU 1600/3	33	3784	35 ³ / ₈ / 23 ⁵ / ₈ / 65	14 ¹ / ₈ / 12 ³ / ₈	14 ¹ / ₈ / 12 ³ / ₈	TK	37	197896	860	○	●	-	7" or 8"
TLU 2000/2	33	4862	35 ³ / ₈ / 29 ¹ / ₂ / 65	14 ¹ / ₈ / 14 ³ / ₄	14 ¹ / ₈ / 18 ¹ / ₄	TK	38	252488	970	○	●	-	7" or 8"
TLU 2137/13	31	4488	35 ³ / ₈ / 29 ¹ / ₈ / 66 ¹ / ₈	20 ¹ / ₈ / 14 ³ / ₄	17 ³ / ₄ / 13 ⁵ / ₈	TK	44	232016	970	○	●	-	7" or 8"
TLU 2450/1	33	6292	42 ¹ / ₂ / 35 ³ / ₈ / 65	17 ³ / ₄ / 16	17 ³ / ₄ / 21 ⁷ / ₈	TK	64	327552	1080	○	●	-	8"
TLU 2480	33	6512	42 ¹ / ₂ / 35 ³ / ₈ / 66 ¹ / ₈	17 ³ / ₄ / 16	17 ³ / ₄ / 21 ⁷ / ₈	TK	66	337788	1080	○	●	-	8"
TLU 2490 (R, L)	33	7392	42 ¹ / ₂ / 38 ⁵ / ₈ / 66 ¹ / ₈	14 ⁵ / ₈ / 14 ³ / ₄	16 ¹ / ₂ , 20 ¹ / ₈ / 28 ¹ / ₂	TK	75	385556	1180	○	●	-	8"
TLU 2637/11	31	5742	42 ¹ / ₂ / 32 ⁵ / ₈ / 66 ¹ / ₈	16 ¹ / ₂ / 15 ³ / ₈	16 ¹ / ₂ / 21 ⁵ / ₈	TK	57	300256	1080	○	●	-	8"
TLU 2687/11	31	6160	42 ¹ / ₂ / 33 ¹ / ₈ / 66 ¹ / ₈	16 ¹ / ₂ , 20 ¹ / ₈ / 15 ³ / ₈	16 ¹ / ₂ / 21 ⁵ / ₈	TK	62	320728	1080	○	●	-	8"
TLU 3233 T (R, L)	31	7590	54 ³ / ₈ / 35 ³ / ₈ / 65	16 ¹ / ₂ , 20 ¹ / ₈ / 15 ³ / ₈	16 ¹ / ₂ / 21 ⁵ / ₈	TK	79	419676	1290	○	●	-	8"
TTU 2700/51	29	8668	61 ³ / ₈ ¹⁾ / 50 ³ / ₄ ¹⁾ / 86 ¹ / ₄	16 ¹ / ₂ / 24 ³ / ₄	16 ¹ / ₂ / 17 ¹ / ₈	TK	70	365084	1400	○	●	-	8"
LLU 1250	31	3014	42 ¹ / ₂ / 26 / 36	- H 7 ⁵ / ₈ / 17 ¹ / ₈	15 ³ / ₈ / 17 ¹ / ₈	TK	33	174012	860	-	-	-	6" or 8" 6"
LIGHTWEIGHT FIREPLACES													
							OUTPUT						
HETTA	41	~2134	~33 ¹ / ₈ / ~27 ¹ / ₂ / 60 ⁵ / ₈	18 ¹ / ₈ / 14 ⁵ / ₈	-	TK	4 lbs/h	12.084 - 38.305 Btu/hr	-	-	-	-	6"
KIISA	41	1364	26 ³ / ₄ / 23 ¹ / ₄ / 57 ¹ / ₈	15 ¹ / ₄ / 9 ¹ / ₂	-	TS	4 lbs/h	11.359 - 26.705 Btu/hr	-	-	-	-	6"
ZEVIO	41	1221	25 ⁵ / ₈ / 22 ⁵ / ₈ / 52 3/4	15 ¹ / ₄ / 9 ¹ / ₂	-	TS	4 lbs/h	11.359 - 26.705 Btu/hr	-	-	-	-	6"

● = STANDARD ○ = OPTIONAL - = NOT POSSIBLE ¹⁾Sizes with benches

ADDITIONAL INFORMATION ON THE TECHNICAL TABLE AND PLANS:

Stone: The soapstone mainly used in the fireplace. **TK** = Tulikivi Matt finished, **TB** = Tulikivi Blue, **TS** = Tulikivi Sky,

Maximum amount of wood (lbs): The maximum amount of wood that can be used in a single heating session, as specified in the operating manual. Note: in lightweight fireplaces, the maximum amount of wood is lbs/hour.

Stored energy (Btu): The amount of energy stored in a fireplace during a single heating session using the amount of wood specified in the operating manual.

Electric element: In the chart, Tulikivi fireplaces and bakeovens marked with can be fitted with electric elements (2.0 kW / 10 A) as an option.

Firebox technology: = Tulikivi flat grate, = Tulikivi whirlbox, additional information on page 54.

Clearances to combustibles: please consult your dealer

Flue recommendation: Always take into account the flue's minimum effective height. The flue connector area has been marked with - in the fireplace's plans. To check which models can be fitted with a flue connector, see the table below. Country-specific, regional and local regulations must be followed. When selecting a flue, you should always consult with your authorized Tulikivi dealer.

Top vent (product code + T): If the footprint drawing shows a red circle, the fireplace can be fitted with an optional top vent feature. The top vent does not increase the base dimensions of flat grate models, if a Tulikivi whirlbox model

is fitted with a top vent, its depth is increased by 105mm(4.13") (marked with ---). In whirlbox models' footprint, the depth measurement of top vent models is stated in brackets ().

Note: Connecting Tulikivi-unit to the masonry or flue tile chimney, use comparable size. All models are UL/ULC listed. For reduced clearances (up to 3"), see TTM 1 or contact your Tulikivi-dealer. Minimum chimney height is 17 feet from firebox floor to the top. Uninsulated outside chimney is recommended to reline and insulate! Weight/overall dimensions/firebox- and bakeoven dimensions are approx. Values, \pm 1%! 1" = 25,4mm / 1 kg = 2,2 lbs. Heat output numbers on homes with 8' ceilings, R-28 insulation in the walls, R-42 insulation in the ceilings, located in a northern climate.

Technical changes: The manufacturer reserves the right to make any technical changes or improvements to the products in this catalog after it has gone into print. The accessories in the images, such as hearth tiles, benches and shelves, are not included in a standard delivery. Local regulations in certain countries may stipulate changes to the place of installation, accessories and flue connector of the fireplaces in this catalog. A hearth protection made of a non-combustible material must be placed in front of a fireplace. Country-specific, regional and local regulations must be followed when determining clearance to combustibles. Soapstone is a natural material which characteristically exhibits slight variations in color and pattern. The product images displayed in this catalog may not completely match the delivered product.

Dimensions in the footprints on the next pages are given in millimeters:	
5 mm = 1/4	100 mm = 3 7/8
10 mm = 3/8	200 mm = 7 7/8
20 mm = 3/4	300 mm = 11 3/4
30 mm = 1 1/8	400 mm = 15 3/4
40 mm = 1 5/8	500 mm = 19 5/8
50 mm = 2	600 mm = 23 5/8
60 mm = 2 3/8	700 mm = 27 1/2
70 mm = 2 3/4	800 mm = 31 1/2
80 mm = 3 1/8	900 mm = 35 3/8
90 mm = 3 1/2	1000 mm = 39 3/8